



**EASY TREAD 2.0**

## **Tyre Scanner Easy Tread 2.0 | Inground**

Automatic tyre tread measurement system with crossing speed up to 8 km/h | Easy Tread for inground installation | with automatic license plate recognition | Connectivity Kit | Live Monitor | ASA network ready

Article number: 1691200049

## Description

**NEW:** Easy Tread 2.0 comes standard with a connectivity kit to digitize and automate your service lane:

- Live monitor of all crossings of multiple Easy Treads in the same workshop network
- 20% faster results
- Ready for ASA interface
- Simplified connection to dealer management systems and 3rd party systems
- Direct connection of monitors and TVs without using the browser
- Optimized statistic functions

The high weight and torque of electric vehicles causes enormous wear on tires and chassis components. The automatic tire diagnosis of every vehicle entering a workshop allows keeping the tire business inhouse and increasing customer loyalty by. The immediate evaluation of the tire wear pattern simultaneously generates service opportunities for wheel alignment and potentially ADAS calibration.

### Easy Tread - Tyre data nonstop

- Automatic tyre wear and diagnosis within seconds
- Clear display of wear information and recommended actions
- Automatic recognition of license plates
- Crossing speed up to 8 km/h (nonstop)
- Measurements in two directions (entering and exiting vehicles)
- High precision thanks to maximum tyre contact area
- Access measurement results without any PC (TV, tablet, smartphone)
- Performance statistics to better manage and optimize your workshop's performance
- No moving parts (low maintenance)
- Quality Made in Germany

### Scope of delivery:

- Easy Tread modules for inground installation (measurement modules, LAN cables, main switch box)
- ANPR camera and center cover
- Connectivity Kit

Note: The foundation frame with article number 1691200010 must be ordered separately. Foundation work is assumed.

## Technical Data

Electrical connection	100 - 230 V   50 - 60 Hz   1 ph
Packaging length	1250 mm
Packaging width	850 mm
Packaging height	1050 mm
Gross weight	258 kg
Length	535 mm
Tyre width max.	450 mm
Height	197 mm
Width	2260 mm
Maximum load per axle	4 t

Working temperature	0 - 40 °C
Max. speed	8 km/h
Weight	230
Test width min. - max.	895-2095 mm
Packaging unit	1 Palette(n)
Accuracy	± 0,25 mm

## Accessories

1691200023 PC trolley for Easy Tread



1691200010 Foundation frame for Easy Tread and VAS 741083 RDS



1691200051 Automatic Cleaning Solution | Easy Tread

