

QB.4

Brake Tester QB.4 | 2200mm | 3,7kW

700mm rollers | 3,7kW | 5,2km/h | 2,5t max. test load | motor brake | AWD detection | speed sensor | ASA v1.2 | galvanized | Premium-coated rollers | with Android App

Numero di articolo: 1691400100

Descrizione

QB.4 - the new benchmark in brake testing

Real-time control via smartphone or tablet

- Ready for mobile Android devices by default
- No cabinets, PCs, or license costs required
- Optional classic display by choice: analog, digital, or TV

No compromise on quality

- Standard motor brake
- Frame and base unit hot galvanized
- Long-lasting premium-coated rollers for high grip and low tire consumption
- Reinforced bearings and high-quality 3.7 kW motors

Next-level power box

- All electronic components safely placed outside roller set
- Flexible display options, no Windows PC needed
- RJ45 Ethernet with ASA Livestream v1.2 interface as standard

Brake testing made easy

- Automatic testing procedure
- No need for remote control
- Automatic detection for all-wheel drive
- Program for electronic parking brakes
- Optional upgrade with 4-point axle weight scales
- Fits in all common foundations

Included as standard. Where others charge extra:

- Motor brake: Increases motor lifespan, simplifies driving axle out of the brake tester
- Galvanized critical components: Protects against corrosion, increases service life
- All-wheel drive detection: Ideally equipped for all-wheel drive and electric vehicles
- Premium-coated rollers: Maximum grip, minimum abrasion
- App use: Replaces complete analog display and PC

Scope of delivery:







- Brake tester with 700mm rollers
- QB.4 control cabinet with ASA Livestream v1.2
- Android app

Dati tecnici

Collegamento elettrico	3 x 400 V 50 - 60 Hz
Lunghezza dell'imballaggio	2420
Larghezza dell'imballaggio	820
Altezza dell'imballaggio	800
Peso lordo	469
Dimensione max. ruota	1000
Sistema di misura	DMS

Lunghezza rulli	700
Elevazione rulli	25
Diametro rulli	205
Carreggiata minima del veicolo	800
Carreggiata massima del veicolo	2200
Dimensione min. ruota	320
Interasse rulli	381
Max. carico assiale verificabile	2
Velocità nominale di prova	5
Max. carico carrabile	4
	-10
Potenza del motore	2 x 3,7
Lunghezza del cavo di alimentazione	15
Streaming live ASA	ja

Accessori

1691601011	Drive-over plate swiveling 700 mm	
1691602000	Edge protection for car brake tester 700 mm	
1691602115	Installation frame for car brake tester 700 mm	
1691601606	Axle load scale 4 sensors	
1691601009	Steel stripy for weights	
1693770644	Tablet per Q.Lign Android 10.1 "	
1691600015	Lifting and lowering device HUS 104 for BD 4xxx and QB.4 brake tester 700mm	