

QB.4

Brake Tester QB.4 | 2800mm | 5,0kW | Spike

1000mm rollers | 5,0kW | 5,2km/h | 4,0t max. test load | motor brake | AWD detection | speed sensor | ASA v1.2 | galvanized | Spike rollers | with Android App

Numero di articolo: 1691400105

Descrizione

QB.4 - the new benchmark in brake testing Real-time control via smartphone or tablet

- Ready for mobile Android devices by default
- No cabinets, PCs, or license costs required
- Optional classic display by choice: analog, digital, or TV

No compromise on quality

- Standard motor brake
- Frame and base unit hot galvanized
- Long-lasting spike rollers for high grip and low tire consumption
- Reinforced bearings and high-quality 5.0 kW motors

Next-level power box

- All electronic components safely placed outside roller set
- Flexible display options, no Windows PC needed
- RJ45 Ethernet with ASA Livestream v1.2 interface as standard

Brake testing made easy

- Automatic testing procedure
- No need for remote control
- Automatic detection for all-wheel drive
- Program for electronic parking brakes
- Optional upgrade with 4-point axle weight scales
- Fits in all common foundations

Included as standard. Where others charge extra:

- Motor brake: Increases motor lifespan, simplifies driving axle out of the brake tester
- Galvanized critical components: Protects against corrosion, increases service life
- All-wheel drive detection: Ideally equipped for all-wheel drive and electric vehicles
- Spike rollers
- App use: Replaces complete analog display and PC

Scope of delivery:





- Brake tester with 1000mm spike rollers
- QB.4 control cabinet with ASA Livestream v1.2
- Android app

Dati tecnici

Collegamento elettrico	3 x 400 V 50 - 60 Hz
Lunghezza dell'imballaggio	3000
Larghezza dell'imballaggio	860
Dimensione max. ruota	1000
Sistema di misura	
Lunghezza rulli	1000
Elevazione rulli	25
Diametro rulli	205

Carreggiata minima del veicolo	800
Carreggiata massima del veicolo	2800
Dimensione min. ruota	320
Interasse rulli	381
Max. carico assiale verificabile	4
Velocità nominale di prova	5
Max. carico carrabile	4
	-10
Potenza del motore	2 x 5,0
Lunghezza del cavo di alimentazione	15
Streaming live ASA	ja

Accessori

1691602112	Drive-over plate pluggable 1000 mm	
1691602151	Edge protection for car brake tester 1000 mm	
1691601606	Axle load scale 4 sensors	
1691601009	Steel strip for weights	
1693770644	Tablet per Q.Lign Android 10.1 "	