



TRUCK

TC1150 HD

Truck tyre changer | 14-42" rim size | extendable up to 56" | 1150mm rim width | 2000kg | 400V

Article number: 1692401009

Description

The TC1150 HD: The ultimate heavy-duty truck tyre changer Self-centering chuck

- Four powerful jaws ensure perfect locking on rims of all shapes and profiles
- Rotates clockwise and anti-clockwise at 4.5 to 9 rpm
- Opens and closes hydraulically with adjustable pressure
- Five grip zones, six different possibilities for clamping the rim

Powerful mounting and demounting tool arm

- Manual adjustment of the tool inclination and direction
- Simply rotate tool to switch between bead breaking roller and bead extraction
- Quick and manual movement of the tool arm closer to or further away from the wheel
- Get the tool arm completely out of the way with one simple move for better access to the wheel
- Powerful bead breaker with 25,000N force in & out

Robust and intuitive cable remote

- Joystick 1 (up & down): Wheel up and wheel down
- Joystick 1 (left and right): Movement of tool carriage
- Joystick 2: Open and close jaws
- Left pedal: rotate anti-clockwise
- Right pedal: rotate clockwise
- Freely movable inside complete working area

Superior versatility

- Effortlessly handles rims up to 42" diameter, extendable up to 56"
- Covers wheels up to 2300mm in diameter and 1150mm in width
- Built to handle weights up to 2000kg

Note: For maximum safety, holes for floor fixation are pre-drilled in the factory by default.

Scope of deliveries:

- Truck mounting lever
- Rim clamp
- 5,3m cable
- 400V plug

Technical Data

| | |
|------------------|---------|
| Packaging length | 1960 mm |
| Packaging width | 2300 mm |
| Packaging height | 1060 mm |
| Gross weight | 1060 kg |

| | |
|---------------------------------------|---------------|
| Length | 2100 mm |
| Height | 1750 mm |
| Width | 1800 mm |
| Max. wheel diameter | 2300 mm |
| Max. rim diameter | 42 " |
| Min. rim diameter | 14 " |
| Weight | 855 kg |
| Motor power | 2,2 - 3 kW |
| Max. wheel width | 1150 mm |
| Max. wheel weight | 2000 kg |
| Rotation speed | 4,5 - 9 U/min |
| Stackable | 2 Stück |
| Units per 20ft container | 4 Stück |
| Units per 40ft container | 10 Stück |
| Min. diameter of centre bore diameter | 122 mm |

Accessories

1692402005 56" clamping jaw extensions | 4 pcs. | TC1150HD



1692402006 OTR Adapter | 4 pcs. | TC1150HD



1692402007 Set internal hole adapter 100mm | TC1150HD



1692402008 Protection kit clamping jaws | 4 pcs. | TC1150HD



1692402010 Clamp for aluminium rims | Truck



1692402011 Rim protection ring | 281mm | for 22,5" aluminium rims

