



HIGH VOLUME

## TC45 | TI Version

Automatic tilt-back tyre changer | 10-27" working range | 15" standard bead breaker | jaw inflation technology | 50-60Hz | 1 Speed

Article number: 1692401013

## Description

### Square turntable with automatic centering jaws

- Clamping range from 10-27"
- Double 80mm cylinders for maximum clamping power
- One rotation speed: 7,5 rpm
- Square shape for easier lever use

### Robust mounting column and head

- Easy tilting via pedal
- Quick vertical and horizontal movement of arm
- Pneumatic locking

### Powerful bead breaker side shovel

- Quick and effective loosening of the bead
- Up to 15" tyre width
- Three-way adjustable blade
- Controlled via pedal
- Anti-skid rubber pad protects tyre and rim

### Full control with four pedals plus side inflation pedal

- Pedal control for rotation, side shovel, column tilting, and clamping
- Removable pedal unit for easier maintenance
- Safety separator for rotation pedal
- Side inflation pedal

### High rigidity by design

- Full metal pedals
- Powerful 50x50mm horizontal arm
- Metal front cover

### Ti: Tire inflation via claws

- Fast and secure gripping of the bead on the rim
- Both hands free during inflation and bead seating
- Minimizes the risk of air leaks or tire bursts
- Easy tire inflation via claws
- 18-liter air tank

### Upgrade options:

- TCX.PRO, PRO2 or PRO3 assistance column
- Side lift
- Tubeless inflation kit
- Roller board

### Scope of deliveries:

- 5x front head protection
- 2x rear head protection
- Standard lever
- Brush
- Plug

Note: unit comes with disassembled pole

## Technical Data

Packaging length	750 mm
Packaging width	1100 mm
Packaging height	1100 mm
Length	1450 mm
Height	1900 mm
Width	1030 mm
Max. wheel diameter	1160
Motor power	1,1 kW
Max. wheel width	381
Rotation speed	7,5 U/min
Space requirement width	1450 mm
Operating pressure	8 - 12 bar
Max. clamping capacity	27 "
Min. clamping capacity	10 "
Min. inner clamping range	12 "
Max. inner clamping range	27 "
Min. outer clamping range	10 "
Max. outer clamping range	24 "
Stackable	2 Stück
Units per 20ft container	30 Stück
Units per 40ft container	60 Stück
Max. torque	1200 Nm
Space requirement length	1850 mm
Turntable height	670 mm

## Accessories

1692402014 Storage kit | for TC22, TC45 and TC47L



1692402029 Quick inflation system | for TC45 and TC47L



1692402031 Bead clamp



1692402032 Mounting head | for motorcycles



1692402380 Set clamping jaws | 4 pcs. | for motorcycles



1692402034 Set clamping jaws | 4 pcs. | for scooters



1692402036 Roller bed | for TC22, TC45 and TC47L



1692402037 Lever | for RFT and UHP tyres



1692402038 Lever | WDK



1692402003 BeadLock Pro | with extension




1692402028 WIKA inflating gun with pressure gauge



1692402027 Rim protector



1692402016 Pneumatic helper arm | for TCX.PRO2 and PRO3



1692402017 Assistance column | TCX.PRO2



1692402018 Assistance column | TCX.PRO



1692402019 Protection kit mounting tool | 10x front + 10x rear



1692402021 Protection kit clamping jaws | 4 pcs | for TC22, TC45 and TC47L



1692402022 Protection for lever



1692402023 Bead breaker shovel protection



1692402025 Quick change kit for mounting head



1692402026 Plastic mounting head | TC22 and TC45



1692402020 Protection | for WDK lever

