



HIGH VOLUME

Wheel balancer G.30P

Entry-level wheel balancer | pneumatic clamping | automatic data arm | 17" touchscreen | Inside line laser | wheel guard with sonar for steel and alloy wheels

Article number: 1692501013

Description

Precise balancing in tight spaces: Compact car wheel balancer

Measurement and balancing:

- Balancing in 4.7 seconds
- Automatic stop of the wheel 15° before correction position
- LED for better visibility when placing weights
- Internal line laser for precise positioning of weights
- Split program for hiding weights behind different spokes

Wheel data recognition:

- Automatic data arm for measuring distance and diameter and weight placement
- Automatic selection of clip-on and adhesive weight program
- Highest measurement accuracy +/- 0.5g

Auto Adaptive Mode:

- Dynamic tolerance adjustment based on weight and size
- Minimizes remaining imbalance to eliminate smallest vibrations noticeable by the driver

Wheel guard with integrated sonar:

- Automatic recognition of rim width in steel and aluminium rims
- Without manual input with measuring gauge
- Closing of wheel guard automatically starts balancing program

17" touchscreen monitor:

- Graphical step-by-step illustrations
- Simplifies correct balancing with guided processes
- Touchscreen usable with gloves on

Quick clamping:

- Pneumatic clamping with 250kg clamping force
- Ensures consistent clamping for all four wheels
- Stable 40mm shaft
- Wheel weights up to 75kg
- Optional with wheel lift

Scope of delivery





- 4 cones Ø43-112,5mm
- Quick-lock sleeve
- Pressure ring
- Rubber ring
- 60g counterweight
- Weight pliers

Technical Data

Electrical connection	230 V 50 - 60 Hz 1 ph
Packaging length	1280 mm
Packaging width	980 mm


Packaging height	1960 mm
Length	1250 mm
Height	1570 mm
Width	1150 mm
Max. wheel diameter	914 mm
Max. rim diameter	30 "
Min. rim diameter	10 "
Weight	110 kg
Motor power	0,15 kW
Max. rim width	20 "
Max. wheel weight	75 kg
Measuring speed	100 U/min
Measuring time	4 s
Balancing accuracy +/-	0 g
Min. rim width	1 "
Shaft diameter	40 mm
Stackable	2 Stück
Units per 20ft container	30 Stück
Units per 40ft container	66 Stück

Accessories

1695653888	Clamping hood large diameter	
1695601012	Wheel lift for wheel balancers	
1692502049	Cone for German OEMs Ø 56.5 / 57 / 66.5 / 70 - 72.5 mm	
1692502037	Universal 3-4-5-6-hole adapter Ø 95 - 120 mm	
1692502000	G.Zero Wheel lift with memory function	



1695655296 QuickPlate | 5-Holes | 96 - 186 mm | 48mm & 58mm



1695656570 All-in-One Centering Kit | Duo Expert 54-78mm | 4x4 | Flange Plates
No.1 & 3



1692502038 3-arm star adapter SR3 | for light trucks | Ø 161 / 170 / 184.15 / 205 /
222.25 / 245 mm

