



BRAKE TESTER

Car brake tester VAS 6360A with PC | for Volkswagen

Maximum test weight/axle 3.5 t, Test Speed 5.2 km/h, Speed sensors | with ASA livestream interface | with trolley and PC | electromagnetic brake, 4x4, 700 mm rollers | Extension possibility to test lanes | New! Power-Box inclusive!

Article number: 1 691 600 019

Description

Brake tester VAS 6360A for track widths up to 2200 mm

The VAS 6360A brake tester handles all VW and Audi vehicles and is designed from high quality components to ensure robustness and long product life even under the harshest environments. The new version of the VAS 6360A additionally provides the user with an intuitive and fast software. The modular approach further allows easy extensions to complete test lanes at any time. Next to the classical noise detectors, side slip plates and suspension tester, the VAS 6360A brake tester can now also integrates seamlessly into the VAS 741 083 automatic tyre diagnosis system. This not only increase your tyre sales but also generates more wheel alignment service opportunities.

Beissbarth Power-Box: the practical new control unit

- All electronic components safely stored in a robust and easily accessible housing
- Compact, robust, and easy to service
- Easy to reach ASA livestream interface integrated into the Power-Box housing
- Comfortable USB interface to easily connect your customer-PC (optional)
- 230V socket to charge laptops of periodical test inspectors and service technicians (separate connection from authorized technician required)
- Easy to access main switch with ON/OFF function
- Integrated storage space for technical documentation

Advantages of the VAS 6360A:

- Automatic AWD detection and 4x4 testing procedure selection
- Electromagnetic motor brake for easy drive-on
- Program for electric parking brakes
- Enforced rollers with tough corundum coating that are gentle on the tyres
- Hot galvanized frame and brake tester components
- 25 mm heightened rear rollers for more precise brake force measurement
- Manual operation with axle wise and single wheel procedure
- Standard equipped with speed sensors and ASA interface (complies with local policies)

Access to numerous features through integration into your workshop PC

- Visualization of testing procedures and results via monitor
- Order management, customer database management, statistic and productivity, print and archive test results and protocols
- Automatic printing of protocols
- Easy integration with the ASA network manager
- Upgrade to full test lanes possible at any time
- Display measurement values without analog display

Scope of delivery:

- Trolley with PC with 27" monitor and printer
- Hot galvanized rollers with 700 mm width
- Power-Box with ASA livestream interface
- Infrared remote control with receiver
- ICPerform Car software license

Please note: this configuration does not include an analog display!

Technical Data

Max. wheel diameter 1000 mm

Weight	420 kg
Max. rim diameter	32 "
Protection class	IP 54 IP
Length	660 mm
Height	2360 mm
Width	250 mm
Test speed	5,2 km/h
Coefficient of friction dry/wet	0,8 / 0,7
Roller length	700 mm
Roller elevation	25 mm
Min. rim diameter	10 "
Max. axle weight	3,5 t
Roller diameter	205 mm
Min. test width	800 mm
Max. test width	2200 mm
Min. wheel diameter	320 mm
Roller axle distance	381 mm
Max. drive-over load	4,0 t
Height difference upper edge of roller to workshop floor	-10 mm

Accessories

1 691 602 000	Edge protection for car brake tester BD 4xxx, 700 mm
1 691 601 010	Drive-over plate pluggable 700 mm
1 691 601 011	Drive-over plate swiveling 700 mm
1 691 602 115	Installation frame for car brake tester BD 4xxx, 700 mm
1 691 601 392	Digital calibration kit for brake tester