



EASY TREAD 2.0

Tyre diagnosis system Easy Tread 2.0 | Above ground

Automatic tyre tread measurement system with crossing speed up to 8 km/h | Easy Tread for above ground installation | with automatic license plate recognition | Connectivity Kit | Live Monitor | ASA network ready

Article number: 1 691 200 050

Description

NEW: Easy Tread 2.0 comes standard with a connectivity kit to digitize and automate your service lane:

- Live monitor of all crossings of multiple Easy Treads in the same workshop network
- 20% faster results
- Ready for ASA interface
- Simplified connection to dealer management systems and 3rd party systems
- Direct connection of monitors and TVs without using the browser
- Optimized statistic functions

The high weight and torque of electric vehicles causes enormous wear on tires and chassis components. The automatic tire diagnosis of every vehicle entering a workshop allows keeping the tire business inhouse and increasing customer loyalty by. The immediate evaluation of the tire wear pattern simultaneously generates service opportunities for wheel alignment and potentially ADAS calibration.

Easy Tread - Tyre data nonstop

- Automatic tyre wear and diagnosis within seconds
- Clear display of wear information and recommended actions
- Automatic recognition of license plates
- Crossing speed up to 8 km/h (nonstop)
- Measurements in two directions (entering and exiting vehicles)
- High precision thanks to maximum tyre contact area
- Access measurement results without any PC (TV, tablet, smartphone)
- Performance statistics to better manage and optimize your workshop's performance
- No moving parts (low maintenance)
- Quality Made in Germany

Scope of delivery:

- Easy Tread modules for above ground installation (measurement modules, LAN cables, main switch box)
- ANPR camera
- Connectivity Kit
- Drive-on ramps

Technical Data

| | |
|-----------------------|---------------------------------|
| Tyre width max. | 450 mm |
| Weight | 160 kg |
| Protection class | IP 65 |
| Depth | 1040 mm |
| Height | 85 mm |
| Packaging unit | 1 Pallet(s) |
| Electrical connection | 100 - 230 V 50 - 60 Hz 1 ph |
| Width | 2245 mm |
| Maximum load per axle | 4 t |
| Operating temperature | 0 - 40 °C |
| Track width | 1080 - 1820 mm |

| | |
|--------------------------------|-----------|
| Accuracy | ± 0,25 mm |
| Max. speed | 8 km/h |
| Packaging length | 850 mm |
| Packaging width | 550 mm |
| Packaging height | 1250 mm |
| Gross weight | 168 kg |
| Country of Origin, customs | DE |
| Number of languages (software) | 18 |

Accessories

| | |
|---------------|---|
| 1 691 200 023 | PC trolley for Easy Tread |
| 1 691 201 023 | Cable tunnel for onground installations of Easy Tread |