



STANDARD SERVICE

Wheel balancer G.20 LCD

Entry-level wheel balancer | mechanical clamping | automatic data arm | LCD control panel | Inside line laser | wheel guard with virtual sonar for steel rims

Article number: 1 692 501 007

Description

Precise balancing in tight spaces: Compact car wheel balancer

Measurement and balancing:

- Balancing in 4.7 seconds
- Automatic stop of the wheel 15° before correction position
- LED for better visibility when placing weights
- Internal line laser for precise positioning of weights
- Split program for hiding weights behind different spokes

Wheel data recognition:

- Automatic data arm for measuring distance and diameter and weight placement
- Automatic selection of clip-on and adhesive weight program
- Highest measurement accuracy +/- 0.5g

Auto Adaptive Mode:

- Dynamic tolerance adjustment based on weight and size
- Minimizes remaining imbalance to eliminate smallest vibrations noticeable by the driver

Wheel guard with virtual sonar:

- Automatic recognition of rim width in steel rims
- Without manual input with measuring gauge or sonar
- Closing of wheel guard automatically starts balancing program

Robust LCD control panel:

- Easy operation
- Built workshop-tough
- Independent of user language

Quick clamping:

- Mechanical clamping with quick-lock nut
- Stable 40mm shaft
- Wheel weights up to 75kg
- Optional with wheel lift

Scope of delivery:

- 3 cones Ø45-111mm
- Quick-lock nut
- Clamping cap
- Pressure ring
- Rubber ring
- 60g counterweight
- Weight pliers

Technical Data

Max. wheel diameter	36" 914mm "
Weight	110 kg
Shaft diameter	40 mm
Measuring speed	100 rpm

Measuring time	4,7 s
Display	LCD
Max. rim width	20 "
Max. rim diameter	30 "
Max. wheel weight	75 kg
Length	1100 mm
Height	1220 mm
Electrical connection	230 V 50 - 60 Hz 1 ph
Width	965 mm
Motor power	0,15 kW
Min. rim diameter	10 "
Number of cones	3
Balancing accuracy +/-	0,5 g
Packaging length	1100 mm
Packaging width	700 mm
Packaging height	1165 mm
Min. rim width	1,5 "
Thread type	40 x 4 TR - Metrisches ISO-Trapezgewinde
Wheel data recording	semi-automatic
Stackable	2 Piece(s)
Units per 20ft container	30 Piece(s)
Units per 40ft container	66 Piece(s)

Accessories

1 692 502 000	G.Zero Wheel lift with memory function
1 692 502 044	Large clamping cap for aluminium rims
1 692 502 029	Spacer sleeve for use with spacer 1692502029
1 692 502 028	Distance ring 40mm in combination with light truck cone 1692502047
1 692 502 036	Spacer for wide rims for use with spacer sleeve 1692502029
1 692 502 046	Light truck cone with 36mm distance ring for ligh truck wheels with center hole Ø 97-170mm
1 692 502 035	Cone 4WD Ø 101 - 119 mm
1 692 502 030	Cones kit for Mercedes-Benz
1 692 502 043	Cones kit Ø 45 - 111 mm 6 pcs.
1 692 502 027	Cones and clamping kit Passenger car Ø 45 - 194 mm
1 692 502 054	Long stud bolt for Peugeot 406 1 Set = 5 pcs
1 692 502 073	Motorcycle and scooter adapter Ø 15 - 35 mm
1 692 502 031	Spacer in combination with light truck cone 1692502047

1 692 502 053	Cone for central hole Ø 43 - 69 mm
1 692 502 025	Cones and clamping kit Truck Ø 202 / 221 / 281 mm
1 692 502 060	Stud adapter kit USA Manual 5 x 101.6 / 139.7 / 165.1 mm 6 x 139.7 / 114.3 mm 4 x 165.1 / 170 mm 3 x 130 mm
1 692 502 056	Stud adapter kit 4-hole Manual 4 x 98 / 100 / 108 / 110 / 114.3 / 120 / 130 mm
1 692 502 057	Stud adapter kit SR5 Manual 5 x 100 / 108 / 112 / 114.3 / 120 / 139.7 / 150 / 160 mm
1 692 502 058	Stud adapter kit 5-hole Manual for Opel 105 / 110 / 115 / 118 / 130 mm
1 692 502 059	Stud adapter kit 5-hole Manual 5 x 98 / 110 / 118 / 120.65 / 127 / 130 / 140 mm
1 692 502 061	Universal 3-4-5-6-hole stud adapter Manual Ø 75 - 210 mm
1 692 502 037	Universal 3-4-5-6-hole adapter Ø 95 - 120 mm
1 692 502 064	Clip-on studs Conical 5 x 103 mm
1 692 502 063	Clip-on studs Conical 5 x 68 mm
1 692 502 062	Clip-on studs Spherical 5 x 123 mm
1 692 502 040	Centering disc Ø 161 mm for 3-arm star adapter SR3
1 692 502 041	Centering disc Ø 130 mm for 3-arm star adapter SR3
1 692 502 039	Centering disc Ø 142 mm for 3-arm star adapter SR3
1 692 502 074	Centering bushes kit 2 x Ø 15 / 16 / 17 / 19.05 / 20 / 22 / 25 / 28 mm 16 pcs.
1 692 502 070	Universal 3-4-5-6-hole stud adapter Pneumatic Ø 75 - 210 mm
1 692 502 050	Centering kit for PSA 5 pcs.
1 692 502 051	Centering kit for Renault 5 pcs.
1 692 502 049	Cone for German OEMs Ø 56.5 / 57 / 66.5 / 70 - 72.5 mm