



QB.4

Brake Tester QB.4 | 2800mm | 5,0kW

1000mm rollers | 5,0kW | 5,2km/h | 4,0t max. test load | motor brake | AWD detection | speed sensor | ASA v1.2 | galvanized | Premium-coated rollers | with Android App

Numero di articolo: 1691400103

Descrizione

QB.4 - the new benchmark in brake testing Real-time control via smartphone or tablet

- Ready for mobile Android devices by default
- No cabinets, PCs, or license costs required
- Optional classic display by choice: analog, digital, or TV

No compromise on quality

- Standard motor brake
- Frame and base unit hot galvanized
- Long-lasting premium-coated rollers for high grip and low tire consumption
- Reinforced bearings and high-quality 5.0 kW motors

Next-level power box

- All electronic components safely placed outside roller set
- Flexible display options, no Windows PC needed
- RJ45 Ethernet with ASA Livestream v1.2 interface as standard

Brake testing made easy

- Automatic testing procedure
- No need for remote control
- Automatic detection for all-wheel drive
- Program for electronic parking brakes
- Optional upgrade with 4-point axle weight scales
- Fits in all common foundations

Included as standard. Where others charge extra:

- Motor brake: Increases motor lifespan, simplifies driving axle out of the brake tester
- Galvanized critical components: Protects against corrosion, increases service life
- All-wheel drive detection: Ideally equipped for all-wheel drive and electric vehicles
- Premium-coated rollers: Maximum grip, minimum abrasion
- App use: Replaces complete analog display and PC

Scope of delivery:

- Brake tester with 1000mm rollers
- QB.4 control cabinet with ASA Livestream v1.2
- Android app

Dati tecnici

| | |
|----------------------------|------------------------|
| Collegamento elettrico | 3 x 400 V 50 - 60 Hz |
| Lunghezza dell'imballaggio | 3000 |
| Larghezza dell'imballaggio | 860 |
| Dimensione max. ruota | 1000 |
| Sistema di misura | DMS |
| Lunghezza rulli | 1000 |
| Elevazione rulli | 25 |
| Diametro rulli | 205 |

| | |
|-------------------------------------|---------|
| Carreggiata minima del veicolo | 800 |
| Carreggiata massima del veicolo | 2800 |
| Dimensione min. ruota | 320 |
| Interasse rulli | 381 |
| Max. carico assiale verificabile | 4 |
| Velocità nominale di prova | 5 |
| Max. carico carrabile | 4 |
| | -10 |
| Potenza del motore | 2 x 5,0 |
| Lunghezza del cavo di alimentazione | 15 |
| Streaming live ASA | ja |

Accessori

| | | |
|------------|--|---|
| 1691602112 | Drive-over plate pluggable 1000 mm |  |
| 1691602151 | Edge protection for car brake tester 1000 mm |  |
| 1691601606 | Axle load scale 4 sensors |  |
| 1691601009 | Steel strip for weights |  |
| 1693770644 | Tablet per Q.Lign Android 10.1 " |  |