



WHEEL BALANCERS

Wheel balancer VAS 741 113

Entry-level wheel balancer | mechanical clamping | automatic data arm | 17" touchscreen | Inside line laser | wheel guard with virtual sonar for steel rims

Article number: 1 692 501 014

Description

Precise balancing in tight spaces: Compact car wheel balancer

Measurement and balancing:

- Balancing in 4.7 seconds
- Automatic stop of the wheel 15° before correction position
- LED for better visibility when placing weights
- Internal line laser for precise positioning of weights
- Split program for hiding weights behind different spokes

Wheel data recognition:

- Automatic data arm for measuring distance and diameter and weight placement
- Automatic selection of clip-on and adhesive weight program
- Highest measurement accuracy +/- 0.5g

Auto Adaptive Mode:

- Dynamic tolerance adjustment based on weight and size
- Minimizes remaining imbalance to eliminate smallest vibrations noticeable by the driver

Wheel guard with virtual sonar:

- Automatic recognition of rim width in steel rims
- Without manual input with measuring gauge or sonar
- Closing of wheel guard automatically starts balancing program

17" touchscreen monitor:

- Graphical step-by-step illustrations
- Simplifies correct balancing with guided processes
- Touchscreen usable with gloves on

Quick clamping:

- Mechanical clamping with quick-lock nut
- Stable 40mm shaft
- Wheel weights up to 75kg
- Optional with wheel lift

Scope of delivery:

- 4 cones Ø43-112,5mm
- Quick-lock nut ProGrip 40x4
- Clamping cap
- Pressure ring
- Rubber ring
- 60g counterweight
- Weight pliers

Technical Data

Max. wheel diameter	36" 914mm "
Weight	110 kg

Shaft diameter	40 mm
Measuring speed	100 rpm
Measuring time	4,7 s
Display	17" Industrial Touchscreen
Max. rim width	20 "
Max. rim diameter	30 "
Max. wheel weight	75 kg
Length	1100 mm
Height	1550 mm
Electrical connection	230 V 50 - 60 Hz 1 ph
Width	960 mm
Motor power	0,15 kW
Min. rim diameter	10 "
Number of cones	4
Balancing accuracy +/-	0,5 g
Packaging length	1100 mm
Packaging width	700 mm
Packaging height	1165 mm
Min. rim width	1,5 "
Thread type	40 x 4 TR - Metrisches ISO-Trapezgewinde
Wheel data recording	Semi-automatic
Stackable	2 Piece(s)
Units per 20ft container	30 Piece(s)
Units per 40ft container	66 Piece(s)

Accessories

1 692 502 191	Wheel lift VAS 741 119/1 with memory function
1 692 502 044	Large clamping cap for aluminium rims
1 695 901 667	Flange extension Off-Road 40 mm
1 695 656 698	Centering system DuoExpert 3 collets 54 - 78 mm
1 695 655 294	Specific clamping plate set QuickPlate variable for 3-, 4-, 5-hole rims 3 pcs.