

Dialogannahme

Q.LIGN T-SERIES

Version 2026.06.02 – Prices on request

Wheel Aligner Q.Lign T | with MultiFit wheel clamps

Q.Lign T.41 with floor mounted support column, turnplates and MultiFit wheel clamps. Operation via 27" monitor. Perfect for independent workshops and tire shops.

Article number: 1690800001



Ultimate productivity - vehicle after vehicle

The T-Series builds on the existing Q.Lign platform and focuses entirely on wheel alignment. With Q.Lign T.41, workshops raise the bar even higher and can thus exploit their full service potential.

Measuring at the highest level

- Camera beam measures permanently from a height of 2.8 meters
- No motor, no winch, no wear and tear
- No up, no down, no injuries or damage
- No movement, no matter if short or long wheelbases

Everything perfectly in sight

- Four wheels, four cameras
- Separate camera for the rear axle for more accurate toe values on the front axle
- Install anywhere within 1.8 to 3.3 meters of the front axle
- Measure and adjust from 0 to 2 meters platform height at any time

Work smarter, not harder

- All targets work on any wheel reduces setup times and setup errors
- Active MEMS Technology: Constant measurement against gravity for uncompromising accuracy
- Caster sweep at floor level without the need for a stool or ladder
- Access to clear and easy-to-understand PDF reports from anywhere inside your shop

The world's first web-based wheel aligner

- Eliminates need for trolley and PC and creates more space
- Incredibly efficient with up to 95% power savings compared to PC-based systems
- Stream-to-X: Access software on any TV, PC, laptop, tablet or smartphone
- Intuitive software, streamlined operations, more productivity
- Easy integration of Q.Lign into your shop's daily processes and system

Space requirement

- Minimum height of 2800mm
- Minimum clearance of 2800mm on four-post lifts

Wheel Aligner Q.Lign T | with Q.Grip clamps

Q.Lign T.41 with floor-mounted support column, templates and Q.Grip wheel clamps. Operation via 27" monitor. For wheel alignment professionals.

Article number: 1690800002



Ultimate productivity - vehicle after vehicle

The T-Series builds on the existing Q.Lign platform and focuses entirely on wheel alignment. With Q.Lign T.41, workshops raise the bar even higher and can thus exploit their full service potential.

Measuring at the highest level

- Camera beam measures permanently from a height of 2.8 meters
- No motor, no winch, no wear and tear
- No up, no down, no injuries or damage
- No movement, no matter if short or long wheelbases

Everything perfectly in sight

- Four wheels, four cameras
- Separate camera for the rear axle for more accurate toe values on the front axle
- Install anywhere within 1.8 to 3.3 meters of the front axle
- Measure and adjust from 0 to 2 meters platform height at any time

Work smarter, not harder

- All targets work on any wheel reduces setup times and setup errors
- Active MEMS Technology: Constant measurement against gravity for uncompromising accuracy
- Caster sweep at floor level without the need for a stool or ladder
- Access to clear and easy-to-understand PDF reports from anywhere inside your shop

The world's first web-based wheel aligner

- Eliminates need for trolley and PC and creates more space
- Incredibly efficient with up to 95% power savings compared to PC-based systems
- Stream-to-X: Access software on any TV, PC, laptop, tablet or smartphone
- Intuitive software, streamlined operations, more productivity
- Easy integration of Q.Lign into your shop's daily processes and system

Q.Grip clamps: the last step before Touchless

- 5x faster than conventional clamps
- No removal of hubcaps
- No scratching of rims
- From 21" to 33" in under a second, no know twisting

Space requirement

- Minimum height of 2800mm
- Minimum clearance of 2800mm on four-post lifts

Q.Lign T-Series



Wheel Aligner Q.Lign T | with MultiFit wheel clamps

Article number: 1690800001



Wheel Aligner Q.Lign T | with Q.Grip clamps

Article number: 1690800002

IMPORTANT NOTES

- Please notice: This list contains spare parts, too.
- Without instruction or assembly.
- Delivery ex works including packaging.

VERSION 2026.06.02 – PRICES ON REQUEST

- Starting from now all previous lists will lose their validity.
- Please read our general terms and conditions in the latest version before ordering; to be found under www.beissbarth.com.

Order number 1 693 602 008 **Print norm** BB XXX / XX.XX.2020 DE · Subject to technical and program changes, errors excepted.

Beissbarth Automotive Testing Solutions GmbH

Friedrichshafener Str. 602
82205 Gilching, Germany
sales@beissbarth.com
www.beissbarth.com

Telefon: +49-(0)89-14901-0
Telefax: +49-(0)89-14901-246

