

# MT 826/826 D/826 DT

## Entry level wheel balancer



- Compact size
- Electronic measuring arm
- Dynamic balancing programs

# MT 826/826 D/826 DT

## Entry level wheel balancer

The MT826/826 D/826 DT are electronic wheel balancers designed for low to medium volume workshop. Thanks to the new extreme versatility and compact size design, the MT 826 electronic wheel balancer series is suitable for working in narrowest environments and with all types of car, motorcycle and lightweight transportation wheels. Supplied with a TFT monitor (MT 826 DT), EASYFIT internal electronic measuring arm and a complete software package including all static and dynamic balancing programs. Thanks to the new wheel cover shape and the new weight holders both units are the perfect equipment in the workshop environment.

### Highlights:

- New Ergonomic wheel cover shape
- New weight holder
- Up to 820 mm diameter
- Max wheel weight 65 kg
- Small footprint
- Internal electronic measuring arm for rim distance & diameter (MT 826D/DT)
- Optional, external electronic measuring arm for rim width
- Many holders for weights and tools
- Monitor TFT 19" (MT 826 DT)



**Weight Holder:**

- Ergonomic weight holder for weights and tools
- Easily accessible

**Keyboard:**

- Intuitive 5 keys-keyboard raised for a better sensibility and accessible from any position

**Scope of delivery:**

- MT 826/826 D/826 DT
- 19" TFT-Monitor / Double Digital LED Display
- Wheel protection
- Mechanic centering flange
- Cones: 3 cones for mechanical locking system
- Weight plier
- Compass
- Calibration weight




## Technical data

|                            | MT 826/826 D                          | MT 826 DT                             |
|----------------------------|---------------------------------------|---------------------------------------|
| Power Supply               | 230V 1ph 50/60 Hz                     | 230V 1ph 50/60 Hz                     |
| Balancing Speed (50-60 Hz) | 208 U/min (50 Hz) / 250 U/min (60 Hz) | 208 U/min (50 Hz) / 250 U/min (60 Hz) |
| Max. Wheel Weight          | 65 Kg                                 | 65 Kg                                 |
| Max. Wheel Diameter        | 820 mm                                | 820 mm                                |
| Max. Wheel Width           | 420 mm                                | 420 mm                                |
| Rim Diameter               | 8" - 26,5" I / 10" - 24" automatisch  | 6" - 40" I / 10" - 24" automatisch    |
| Rim Width                  | 2" - 20" I / 1 - 20" automatisch      | 1" - 24" I / 1 - 20" automatisch      |
| Accuracy                   | 1 g / 0,05 oz                         | 1 g / 0,05 oz                         |
| Max. Dimensions (WxDxH)    | 1100 x 1270 x 1280                    | 1100 x 1270 x 1370                    |

# Accessories

PN: 1695 653 449



Light transport vehicle cone  
(88 - 132 mm)

PN: 1695 107 200



Cone spacer

PN: 1695 854 849



Set of light truck cones  
(88 - 174 mm)

PN: 1695 901 667



Kit of Off-Road cones from the back  
incl. pins (40mm) distance ring,  
polyamide spacer

PN: 1695 554 043



3-, 4-, 5-hole Flange

PN: 1695 655 294



Set of QuickPlates  
(4-, 5-, 6-holes-plates)

PN: 1695 600 598



Electronic rim width measurement  
arm (MT 826 D/DT)

PN: 1695 656 698



DuoExpert system (3 collets in a  
case, 54 - 78 mm)

PN: 1695 656 570



Kit demo box for passenger car

PN: 1695 654 039



Basic motorbike wheel centring kit  
(14 mm)

PN: 1695 654 060



Monolever wheel centring kit + shaft  
(19 mm)

PN: 1695 606 300



Fourth cone (Ø 120 - 174 mm)

Beissbarth GmbH  
Hanauer Straße 101  
80993 München  
Germany

Tel. +49-89-149 01-0  
Fax +49-89-149 01-240

[www.beissbarth.com](http://www.beissbarth.com)  
[sales@beissbarth.com](mailto:sales@beissbarth.com)

